


SELLO MECÁNICO PARA BOMBAS FLYGT / GRINDEX

TIPO SE / SEEXE



D1	D2	D3	D4	D5	L1	L2
20	55	392	61.5	34.5	54	
25	60	505	66.0	36	56.5	
35	80	615	91.4	44.5	66.7	
45	90	695	100.2	—	85	
60	115	826	127.7	—	86.5	
90	145	1352	156.5	64.6	90	

Medidas en milímetros

Sello de gran aplicación en la industria minera y la industria en general. Compatible con los modelos estándar de bombas Grindex y Flygt.

Presión: Hasta 180 PSI (12 bar)

Temperatura: -22°F a -356°F (-30°C a 180°C)

Velocidad: 1968 fpm (10 m/s)



MATERIALES

- ▶ **Partes metálicas:** AISI 304.
- ▶ **Caras de sellado:** Carbón (Grafito) / Cerámica.
- ▶ **Sellos elastoméricos:** Viton / Nitrilo (según necesidad).




VENTAJAS


- ▶ Intercambiable con otros modelos comerciales.
- ▶ Fácil adquisición.
- ▶ Alta resistencia y durabilidad.




MODELOS Y DIMENSIONES



20-25mm



35mm



45-60 mm

MODELO	MODELOS DE BOMBAS Y MEZCLADORES FLYGT Y GRINDEX
SEEXE-20	1520, 2610, 2620, 2630, 2640, 4610 & 4620
SEEXE-25	2660, 4630 & 4640
SEEXE-35	2670, 3153, 5100.210, 5100.211, 5100.220 & 5100.221
SEEXE-45	3171, 4650, 4660, 5100.250, 5100.251, 5100.260 & 5100.261
SEEXE-60	3202, 4670, 4680, 5100.300, 5100.310, 5150.300 & 5150.310
SEEXE-90	3301, 5150.350, 550.360



EN PROSMEC S.A.S.
CALIDAD, PRECIOSIÓN Y CONFIANZA
EN CADA PROCESO.



Cali, Valle del Cauca
Colombia



314 569 3906



www.prosmecsas.com